



Personal Information

Name: _____

Phone Number: _____ Email Address: _____

7 character password: _____
case sensitive for website order tracking

Authorized Seven Retailer: _____

Salesperson: _____

Your Seven Model (please choose one)

Road ☐ 622 SLX ☐ Elium SLX ☐ Elium SL
☐ Axiom SLX ☐ Axiom SL ☐ Axiom S ☐ Axiom

Road Mid-Reach ☐ RedSky PRO ☐ RedSky SLX ☐ RedSky SL ☐ RedSky S ☐ RedSky

Cyclocross ☐ Mudhoney PRO ☐ Mudhoney SLX ☐ Mudhoney SL ☐ Mudhoney S ☐ Mudhoney

Mixed Terrain ☐ Evergreen PRO ☐ Evergreen SLX ☐ Evergreen SL ☐ Evergreen S ☐ Evergreen

Touring ☐ Expat SL ☐ Expat S ☐ Expat

Travel ☐ Airheart PRO ☐ Airheart SLX ☐ Airheart SL ☐ Airheart S ☐ Airheart

Commuter and Urban ☐ Cafe Racer SL ☐ Cafe Racer S ☐ Cafe Racer

Tandem ☐ Axiom 007 SL ☐ Axiom 007

Function and Use (please choose one)

Function and Use	Handling	Function and Use	Handling
<input type="checkbox"/> Road Standard	5	<input type="checkbox"/> Triathlon Advanced Position	5
<input type="checkbox"/> Road Performance	6	<input type="checkbox"/> Cyclocross Racing	5
<input type="checkbox"/> Road Endurance	4	<input type="checkbox"/> Cyclocross Expedition	4
<input type="checkbox"/> Light Touring	4	<input type="checkbox"/> Commuting City	5
<input type="checkbox"/> Loaded Touring	3	<input type="checkbox"/> Commuting Rural	4
<input type="checkbox"/> Triathlon Short Course	5	<input type="checkbox"/> Mixed Terrain	4

Frame Size Information

Top Tube Length: cm

Head Tube Length: SSP Std. Other Head Tube Extension (cm): 0.0 1.0


Seat Tube Angle: SSP Std. Other Top Tube Slope: SSP Std. Other

Customized Tubeset Details


Average number of miles ridden per week in season:

Age: Weight: Gender: Male Female

Drivetrain Stiffness



Vertical Compliance



Weight-to-Performance



○ denotes default

Frame Options

- Wheel Size** ☐ 700c ☐ 650b ☐ 650c
- Toe overlap is acceptable** Yes No
- Head Tube** 1-1/8" 44mm
- Rear Axle Spacing** 130 135
 120 145 (Tandem)
- Bottom Bracket** Standard Threaded Eccentric[‡]
 BB30[‡] PressFit 30[‡]
- Dropouts** Road, Standard Track
 Slider Dropouts[‡]

Brakes

- Road, Standard Road, Medium Reach (47-57mm)
- V-Brake / Cantilever Disc Brake, ISO
- Low-Mount Disc Brake, ISO
- Disc brake rotor diameter (mm) 140 160 180 203

Cable Routing

- Road style: Brake Cable Stops at 7:00 on Top Tube
- Threaded Adjusters on Down Tube at Head Tube
- Cable Stops on Head Tube (default for SLX frames)
- Internal routing for Shimano Di2 - Battery located on:
 Inside Seat Post Top of Down Tube
 Bottom of Down Tube Underside of Chain Stay
- Internal routing for Campagnolo EPS - Battery located on:
 Inside Seat Tube Top of Down Tube Bottom of Down Tube
- Cyclocross style: all cables on Top of Top Tube

Frame Options

- Water Bottle Mounts: 0 1 2 3
- Pump Peg Chain Hanger Fender Mounts

Rack Options:

- Rack Mounts: On Dropouts On Seat Stays

Upcharge Options

- S&S BTC™ Couplings[‡] S&S Case Package Belt Drive Compatible[‡]

Decal Options

- Upcharge applies to custom colors. See Brochure for details.**
- Black w/ White Outline Blasted[‡] Other: _____

Optional name decal to say: _____

- Black Script lettering Drive side only
- White Block lettering Both sides of top tube

Paint[‡]

Color(s): _____

Scheme: _____

See examples of Seven's wide range of paint and decals on our website <http://sevencycles.com/paint>. Downloadable templates are available.

Notes:

Signature

Your signature indicates that all information is true and correct to the best of your knowledge.

Date

Services

- Seven's Three-year Protection Plan - \$495**
TYP protects against unforeseen, unlucky, or unfortunate damage to your frame for three years.

Components Will You be Using

Fork

- Seven 5E Carbon Seven CX 'Cross - Canti/V-Brake only
- Seven 5E Medium Reach Seven 5E 650c
- Fender mounts (not available on Seven 'CX Cross) No Yes
- Other Fork (please specify model): _____

Seat Post

- Integrated Seat Post[‡]
Available only on Elium SLX & SL, 622 SLX, Mudhoney SLX & PRO, and Evergreen PRO
- Seven Titanium, Custom Length
- Other: Set Back Center Mount

Stem

- Custom Seven Titanium
- Stem angle: 96° Other: Length:
- Stiffness: S2 Std S3 Extra Stiff
- Seven Aluminum Ti bolt upgrade (Aluminum stem only)
- Stem Sourced by retailer: Length: _____ Angle: _____

Handlebar

- Seven Aluminum Road Bar Width: 38 40 42 44
- Custom Seven Tiberius Bar* (Use appropriate Bar order form)
- Bar Sourced by retailer: _____

Spacers

- Seven Titanium Spacers Aluminum

Racks

- Custom Seven Rear Rack Custom Seven Front Rack
- Stainless Steel Ti Stainless Steel Ti

Seven Component Decal Color

- Silver Black Red

Additional Components

- Drivetrain
- Geared Single
- Belt Internal, please specify: _____

Gruppo: _____

Crank Set: _____ single double triple

Front Derailleur Mount:

- High Clamp Low Clamp None

Tire Width: _____

‡ Upcharge applies to frame. Components and accessories are separate.



Tel: 617.923.7774

Fax: 617.923.7757

email: customs@sevencycles.com