



## Personal Information

Name: \_\_\_\_\_

Phone Number: \_\_\_\_\_ Email Address: \_\_\_\_\_

7 character password: \_\_\_\_\_  
case sensitive for website order tracking

Authorized Seven Retailer: \_\_\_\_\_

Salesperson: \_\_\_\_\_

## Your Seven Model (please choose Wheel Size and Model)

### Wheel Size

29"  27.5"  26"

Dual Wheel Use Primary Wheel Size \_\_\_\_\_

### Mountain/Expedition

622m SLX  Sola SLX  Sola+ SL  Treeline SL  
 622m SL  Sola SL  Sola+ S  Treeline S  
 Sola S  
 Sola (steel)

### Tandem

Sola SL 007  Sola 007

## Function and Use (please choose one)

Function and Use	Handling	Function and Use	Handling
<input type="checkbox"/> XC Race, Technical	6	<input type="checkbox"/> Loaded Touring	3
<input type="checkbox"/> XC Mountain, Standard	5	<input type="checkbox"/> Commuting City	5
<input type="checkbox"/> XC Expedition	4	<input type="checkbox"/> Commuting Rural	4
<input type="checkbox"/> All-Mountain Hardtail	3		

## Frame Size Information

Top Tube Length (in): \_\_\_\_\_ Seat Tube Angle:  SSP Std.  Other \_\_\_\_\_

## Customized Tubeset Details

Average number of miles ridden per week in season: \_\_\_\_\_


Age:  Weight:  Gender:  Male  Female

☉ denotes default


### Drivetrain Stiffness



### Vertical Compliance



### Weight-to-Performance



## Frame Options

### Head Tube

44 mm

### Rear Axle Spacing

148 mm Boost  142 x 12 mm Thru Axle dropouts  
 135 mm  157 mm  145 mm (Tandem)

### Dropout Option

Thru Axle  Mountain, Standard QR

### Brakes

Flat Mount with Adapter  
 Disc, ISO  Low-Mount Disc, ISO  
 Both Disc & V-brake  V-brake only  
Disc brake rotor diameter (mm)  140  160  180  203

### Brake Actuation

Zip Tie Guides on top of chain stay  Zip Tie Guides on bottom of chain stay  
 Cable Stops

### Bottom Bracket

Standard Threaded  T47<sup>‡</sup>  PressFit 30<sup>‡</sup>  
 Eccentric<sup>‡</sup>  BB30<sup>‡</sup>  Pinion<sup>‡</sup>

### Bottom Bracket Length

73 mm  68 mm  100 mm

### Cable Routing

Full Length Cable Housing via Zip Tie Guides on Down Tube  
 Di2  Top of Top Tube  Bottom of Top Tube  
 Derailleur Cable Stops on Down Tube, Brake Cable Routing at 10:30 on Top Tube

## Frame Options

Water Bottle Mounts:  0  1  2  3  Chain Hanger  Fender Mounts

### Rack Options:

Rack Mounts:  On Dropouts  On Seat Stays

### Upcharge Options

XX Package Options<sup>‡</sup>  
 Dropped Chainstay<sup>‡</sup>  Chopped Chainstay<sup>‡</sup>  Curved Seat Tube<sup>‡</sup>  
 Moto Seat Stays<sup>‡</sup>  1" Fastback Dropouts<sup>‡</sup>  Curved Top Tube<sup>‡</sup>  
 S&S BTC™ Couplings<sup>‡</sup>  S&S Case Package  Belt Drive Compatible<sup>‡</sup>

### Decal Options

Upcharge applies to custom colors. See Brochure for details.

Black w/ White Outline  Blasted<sup>‡</sup>  Other: \_\_\_\_\_

Optional name decal to say: \_\_\_\_\_

Black  Script lettering  Drive side only  
 White  Block lettering  Both sides of top tube

### Paint<sup>‡</sup>

Color(s): \_\_\_\_\_

Scheme: \_\_\_\_\_

See examples of Seven's wide range of paint and decals on our website <http://sevencycles.com/paint>. Downloadable templates are available.

<sup>‡</sup> Upcharge applies to frame. Components and accessories are separate.

## Services

### Seven's Three-year Protection Plan - \$495

TYP protects against unforeseen, unlucky, or unfortunate damage to your frame for three years.

## Components Will You be Using

### Fork

Fork make and model: \_\_\_\_\_

Travel:  100mm  120mm  Other \_\_\_\_\_

### Seat Post

27.2mm  30.9mm

Seven Titanium, Custom Length

Other:  Set Back  Center Mount

Dropper Routing and Preferred Dropper Travel \_\_\_\_\_

### Stem

Stem angle:  96°  Other: \_\_\_\_\_ Length: \_\_\_\_\_

Seven Aluminum

Stem Sourced by retailer: Length: \_\_\_\_\_ Angle: \_\_\_\_\_

### Handlebar (Use appropriate bar order form)

Custom Titanium Flat Bar

### Will you be using another type of handlebar?

Standard flat handlebar \_\_\_\_\_

Riser bar, how much rise? \_\_\_\_\_

Spacers  Titanium  Aluminum

## Seven Component Decal Color

Silver  Black  Red

## Additional Components

### Drivetrain

Geared  Single

Belt  Internal, please specify: \_\_\_\_\_

Maximum Chaining Size: \_\_\_\_\_

Power Meter Model: \_\_\_\_\_

Gruppo: \_\_\_\_\_

Crank Set: \_\_\_\_\_  single  double  triple

### Front Derailleur Compatibility

Low Clamp (recommended)  None

Max Tire Width: \_\_\_\_\_

### Notes:

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

### Signature

### Date

Your signature indicates that all information is true and correct to the best of your knowledge.



Tel: 617.923.7774 | Fax: 617.923.7757