



Signature Size Order Form: Road, Gravel, Cross, & Touring

Denotes default. This is what you will receive unless you specify otherwise.

2018 Version 1.1

Personal Information

Name: _____

Phone Number: _____ Email Address: _____

7 character password: _____ case sensitive for website order tracking

Authorized Seven Retailer: _____

Salesperson: _____

Your Seven Model (please choose one)

Road 622 SLX 622 SL 622 S
 Axiom SLX Axiom SL Axiom S Axiom

Road Mid-Reach RedSky PRO RedSky SLX RedSky SL RedSky S RedSky
Cyclocross Mudhoney PRO Mudhoney SLX Mudhoney SL Mudhoney S Mudhoney

Mixed Terrain Evergreen PRO Evergreen SLX Evergreen SL Evergreen S Evergreen

Touring Expat SL Expat S Expat

Travel Airheart PRO Airheart SLX Airheart SL Airheart S Airheart

Commuter and Urban Greenway SL Greenway S Greenway

Tandem Axiom 007 SL Axiom 007

Function and Use (please choose one)

Function and Use	Handling	Function and Use	Handling
<input type="checkbox"/> Road Standard	5	<input type="checkbox"/> Cyclocross Racing	5
<input type="checkbox"/> Road Performance	6	<input type="checkbox"/> Cyclocross Expedition	4
<input type="checkbox"/> Road Endurance	4	<input type="checkbox"/> Light Touring	4
<input type="checkbox"/> Gravel	4	<input type="checkbox"/> Loaded Touring	3
<input type="checkbox"/> Mixed Terrain	4	<input type="checkbox"/> Commuting	5
		<input type="checkbox"/> Triathlon	5

Frame Size Information

Top Tube Length: cm

Head Tube Length: SSP Std. Other Head Tube Extension (cm): 0.0 1.0


Seat Tube Angle: SSP Std. Other Top Tube Slope: SSP Std. Other

Customized Tubeset Details


Average number of miles ridden per week in season:

Age: Weight: Gender: Male Female


Drivetrain Stiffness



Vertical Compliance



Weight-to-Performance



denotes default

Frame Options

Wheel Size 700c 650b

Toe overlap is acceptable Yes No

Head Tube 44mm 1-1/8"

Rear Axle Spacing 130 135 142

120 145 (Tandem)

Bottom Bracket Standard Threaded

T47[‡] BB30[‡]

PressFit 30[‡] Eccentric[‡]

Road, Standard Flat Mount Disc

Track Slider Dropouts[‡]

Dropouts

Brakes

Road, Standard Road, Medium Reach (47-57mm)

Flat Mount Disc Disc Brake, ISO

Low-Mount Disc Brake, ISO

Disc brake rotor diameter (mm) 140 160 180 203

Cable Routing

Road style: Brake Cable Stops at 7:00 on Top Tube

Threaded Adjusters on Down Tube at Head Tube

Cable Stops on bottom of down tube at Head Tube

Internal routing for Shimano D12

Internal routing for Campagnolo EPS

eTap style: no routing for derailleurs

Cyclocross style: all cables on Top of Top Tube with pulley

Frame Options

Water Bottle Mounts: 0 1 2 3

Pump Peg Chain Hanger Fender Mounts

Rack Options:

Rack Mounts: On Dropouts On Seat Stays

Upcharge Options[‡]

XX Package Options Dropped Chainstay

Chopped Chainstay Curved Seat Tube

Moto Seat Stays 1" Fastback Dropouts

S&S Couplings S&S Case Package Belt Drive

Decal Options

Upcharge applies to custom colors. See website for details.

Black w/ White Outline Blasted[‡] Other: _____

Optional name decal to say: _____

Black Script lettering Drive side only

White Block lettering Both sides of top tube

Paint[‡]

Color(s): _____

Scheme: _____

See examples of Seven's wide range of paint and decals on our website <http://sevencycles.com/paint>. Downloadable templates are available.

Components Will You be Using

Fork

Seven 5E Carbon

Seven Matador

Seven 5E Medium Reach

Other Fork (please specify model): _____

Seat Post

Seven Titanium, Custom Length

Other: Set Back Center Mount

Stem

Seven Aluminum

Stem Sourced by retailer: Length: _____ Angle: _____

Handlebar

Seven Aluminum Road Bar Width: 38 40 42 44

Bar Sourced by retailer: _____

Spacers

Seven Titanium Spacers Aluminum

Seven Component Decal Color

Silver Black Red

Additional Components

Drivetrain

Geared Single

Belt Internal, please specify: _____

Gruppo: _____

Crank Set: _____ single double triple

Front Derailleur Mount:

High Clamp Low Clamp None

Tire Width: _____



Tel: 617.923.7774

Fax: 617.923.7757

[‡] Upcharge applies to frame. Components and accessories are separate.